

Coaxial Cable SUCOFEEED_7/8_LA

Description

Corrugated coaxial cable - low attenuation



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Copper	Tube	typ. 9.5 mm
Dielectric	SPE (Foamed Polyethylene)		typ. 22.7 mm
Outer conductor	Copper	Tube (c)100%	typ. 25.4 mm
Jacket	PE-LD (Low-density polyethylene)	RAL 9005 - bk	27.9 mm +/- 0.4

Print: HUBER+SUHNER_SUCOFEEED_7/8_LA_#batch-number#_#metric-length#

Electrical Data

Impedance	50 Ω +/- 1
Operating Frequency	≤ 5 GHz
Capacitance	typ. 73.8 pF/m
Inductance	typ. 0.2 μH/m
Velocity of signal propagation	typ. 90.3 %
Signal delay	typ. 3.7 ns/m
Insulation resistance	≥ 3 x 10 ⁶ MΩm
Screening effectiveness	≥ 120 dB
Operating voltage	≤ 3 kVrms (at sea level)
Test voltage	6 kVrms (50 Hz/1 min)
Outer conductor resistance DC	≤ 1.12 Ω/km
Inner conductor resistance DC	≤ 1.35 Ω/km

Mechanical Data

Weight	≤ 48 kg/100 m	
Bending Radius	static	≥ 120 mm
Bending Radius	repeated (for ≤ 15 bendings)	≥ 250 mm
Tensile strength	≤ 1500 N	
Bending force moment	≤ 19 Nm	

Environmental Data

Temperature range	-55 °C... +85 °C
Installation temperature	-40 °C... +60 °C
Halogen test	IEC 60754-1
2011/65/EU (RoHS)	compliant

Additional Information

Remarks

(For details contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group M25 23 mm / 50 Ohm

Suitable Tools

Cable tool 74_Z-0-23-17

Suitable Grounding Kit

Cable grounding kit 9076.99.N078 9076.99.P078

Coaxial Cable SUCOFEEED_7/8_LA

Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p/f^{0.5})$]

Coefficients:

a = 0.03376 typ.

b = 0.0037 typ.

f_{max.} = 5

P ≤ at 1GHz = 2440

Frequency (GHz)	Nom. attenuation (dB / 100 m)	Nom. attenuation (dB / 100 ft)	Max. CW power (watt)
	sea level 20° C ambient temperature	sea level 20° C ambient temperature	sea level 40° C ambient temperature
0.100	1.10	0.34	7716
0.150	1.36	0.42	6300
0.200	1.58	0.48	5456
0.400	2.28	0.70	3858
0.450	2.43	0.74	3637
0.500	2.57	0.78	3451
0.700	3.08	0.94	2916
0.800	3.32	1.01	2728
0.900	3.54	1.08	2572
1.000	3.75	1.14	2440
1.500	4.69	1.43	1992
1.700	5.03	1.53	1871
1.800	5.20	1.58	1819
2.000	5.51	1.68	1725
2.200	5.82	1.77	1645
2.500	6.26	1.91	1543
3.000	6.96	2.12	1409

Matrix typical Return Loss

Frequency Range (MHz)	Frequency Range (MHz)	Frequency Range (MHz)	Frequency Range (MHz)
380 to 470	806 to 960	1710 to 2200	2500 to 2690
typ. 28.5 dB	typ. 26.9 dB	typ. 25.6 dB	typ. 25 dB